



1/2"–2" Brass Construction
All Stainless Steel with suffix – S516
0/0–4" Stainless Steel construction only

Cl. I†, Div. 1 & 2, Groups A,B,C,D Explosionproof
Cl. II, Div. 1, Groups E,F,G Dust-Ignitionproof
Cl. II, Div. 2, Groups F,G Wet Locations
Cl. III

1" to 2" (Brass and S516) – Class I, Division 1 & 2, Groups C,D
2 1/2" to 4" (Stainless Steel) – Class I, Division 1 & 2, Groups C,D

All sizes also for use in Class II, Division 1, Groups E,F,G, Division 2, Groups F,G and Class III
● UL Standard: 886



Certifications and Complies:

- NEC:
1/2" and 3/4" (Brass and S516) – Class I, Division 1 & 2, Groups A,B,C,D

ECGJH (Male connections both ends)

Flexible Length	Size	Cat. #	Flexible Length	Size	Cat. #	Flexible Length	Size	Cat. #
4	1/2	ECGJH14	18	1	ECGJH318	27	2 1/2	ECGJH727
4	3/4	ECGJH24	18	1 1/4	ECGJH418	27	3	ECGJH827
6	1/2	ECGJH16	18	1 1/2	ECGJH518	27	4	ECGJH1027
6	3/4	ECGJH26	18	2	ECGJH618	30	1/2	ECGJH130
6	1	ECGJH36	18	2 1/2	ECGJH718	30	3/4	ECGJH230
8	1/2	ECGJH18	18	3	ECGJH818	30	1	ECGJH330
8	3/4	ECGJH28	18	4	ECGJH1018	30	1 1/4	ECGJH430
8	1	ECGJH38	21	1/2	ECGJH121	30	1 1/2	ECGJH530
10	1/2	ECGJH110	21	3/4	ECGJH221	30	2	ECGJH630
10	3/4	ECGJH210	21	1	ECGJH321	30	2 1/2	ECGJH730
10	1	ECGJH310	21	1 1/4	ECGJH421	30	3	ECGJH830
12	1/2	ECGJH112	21	1 1/2	ECGJH521	30	4	ECGJH1030
12	3/4	ECGJH212	21	2	ECGJH621	33	1/2	ECGJH133
12	1	ECGJH312	21	2 1/2	ECGJH721	33	3/4	ECGJH233
12	1 1/4	ECGJH412	21	3	ECGJH821	33	1	ECGJH333
12	1 1/2	ECGJH512	21	4	ECGJH1021	33	1 1/4	ECGJH433
12	2	ECGJH612	24	1/2	ECGJH124	33	1 1/2	ECGJH533
12	2 1/2	ECGJH712	24	3/4	ECGJH224	33	2	ECGJH633
12	3	ECGJH812	24	1	ECGJH324	33	2 1/2	ECGJH733
12	4	ECGJH1012	24	1 1/4	ECGJH424	33	3	ECGJH833
15	1/2	ECGJH115	24	1 1/2	ECGJH524	33	4	ECGJH1033
15	3/4	ECGJH215	24	2	ECGJH624	36	1/2	ECGJH136
15	1	ECGJH315	24	2 1/2	ECGJH724	36	3/4	ECGJH236
15	1 1/4	ECGJH415	24	3	ECGJH824	36	1	ECGJH336
15	1 1/2	ECGJH515	24	4	ECGJH1024	36	1 1/4	ECGJH436
15	2	ECGJH615	27	1/2	ECGJH127	36	1 1/2	ECGJH536
15	2 1/2	ECGJH715	27	3/4	ECGJH227	36	2	ECGJH636
15	3	ECGJH815	27	1	ECGJH327	36	2 1/2	ECGJH736
15	4	ECGJH1015	27	1 1/4	ECGJH427	36	3	ECGJH836
18	1/2	ECGJH118	27	1 1/2	ECGJH527	36	4	ECGJH1036
18	3/4	ECGJH218	27	2	ECGJH627			

Application:

EC couplings are used:
● in hazardous areas where a flexible member is required in a conduit system to accomplish difficult bends, or to allow for movement or vibration of connected equipment or units

Features:

- Rugged design to withstand explosive pressure (Class I)
- Mechanical abuse
- Liquid-tight for wet locations
- For use where lack of space makes use of rigid conduit difficult
- Wire duct liner in sizes 1/2" to 2" insulates against grounds and burn-through from short circuit
- No bonding jumpers required, metallic braid provides continuous electrical path
- ECGJH combination has two threaded male end fittings
- ECLK combination has one female union and one male threaded end fitting

Standard Materials:

- End fittings:
1/2" to 2" – forged brass
2 1/2" to 4" – stainless steel
- Female unions:
1/2" to 1" – steel
1 1/4" to 4" – Feraloy iron alloy
- 1/2" to 2" have bronze braid covering and flexible brass inner core; packing is woven cotton braid impregnated with asphalt.
- 2 1/2" to 4" have a Type 304 stainless steel braid.


Standard Finishes:

- Brass and bronze – natural
- Steel – electrogalvanized with chromate treatment
- Feraloy iron alloy – electrogalvanized with aluminum acrylic paint
- Stainless steel – natural

Options:

Description Suffix to be Added to Cat. #
All stainless steel S516
For severely corrosive locations, a flexible PVC protective coating will be supplied S758
Special coupling lengths available up to 144 inches.
To order, change last two digits in any standard catalog number to the two or three digit length desired in whole inches i.e. To order a 3/4" trade size 110 inches long, use catalog number ECGJH2110

Dimensions



†See certifications and compliances.