



CAJA OVAL "S" CON TAPA. PARA TUBO RIGIDO E IMC.

OVAL CONDUIT BODIES "S" WITH COVER. FOR USE WITH RIGID AND IMC CONDUIT

- Material:
 - Cuerpo: Aluminio inyectado a presión (diecast).
 - Tapa: Lámina de Aluminio.
 - Tornillos: Galvanizados.

- Acabados: Pintura electrostática epoxica/poliéster polimerizada.
- Rosca NPT para usarse con tubo conduit RIGIDO e IMC.
- Tapa y tornillos ensamblados.
- Empaque: Proporciona hermetismo al agua.
- Fabricación en base a: UL 514 A
CAN/CSA-C22.2 No. 18-92
- Adecuado para áreas clasificadas clase I, división 2 si la instalación cumple con NEC 501-4 (b).

- Material:
 - Body: Diecast aluminum.
 - Cover: Sheet aluminum.
 - Screws: Galvanized steel.
- Finish: Electrostatic powder epoxy/poliéster coating.
- NPT threaded for use with RIGID and IMC conduit.
- Cover and screws assembled.
- Gasket: Provide rain tight.
- Manufactured in compliance with: UL 514 A
CAN/CSA-C22.2 No. 18-92
- Suitable for classified location use in class I, division 2 areas if installed in compliance with NEC 501-4 (b).

Figura Figure	Catalogo Catalog	Medida nominal Hub size		Volumen Volume		Peso x 100 pzas. Weight x 100 pcs.		Unit Ctn.	Ship Ctn.	Std. Pkg.	Num. y calib. max. conduct. Max. No. and sze. conduct.
		mm	inch	cm ³	cu. in	kg	Lb	Pzas. Pcs.	Pzas. Pcs.	Pzas. Pcs.	
OLL 	030.010.050	12.7 S	1/2 S	65.5	4.0	10.9	24.0	10	40	52	3, #8 AWG
	030.010.075	19.0	3/4	111.3	6.8	17.3	38.2	5	40	24	3, #6 AWG
	030.010.100	25.4	1	185.0	11.3	22.5	49.6	5	20	40	3, #4 AWG
	030.010.125	31.8	1 1/4	512.6	31.3	49.9	110.1	2	8	15	3, #2 AWG
	030.010.150	38.1	1 1/2	537.2	32.8	57.4	126.6	2	8	15	3, #1/0
	030.010.200	50.8	2	1208.8	73.8	122.3	269.7	1	4	6	3, #4/0
	030.010.250	63.5 S	2 1/2 S	1610.1	98.3	184.4	406.7	1	3	4	3, #4/0
	-	63.5 L	2 1/2 L	2866.5	174.9	325.5	716.1	1	-	1	3, #300 MCM
	030.010.300	76.2 S	3 S	1850.9	113.0	230.4	508.1	1	3	4	3, #4/0
	-	76.2 L	3 L	2866.5	174.9	285.5	628.1	1	-	1	3, #250 MCM
OLR 	030.015.050	12.7 S	1/2 S	65.5	4.0	10.9	24.0	10	40	52	3, #8 AWG
	030.015.075	19.0	3/4	119.5	7.3	16.8	37.1	5	40	24	3, #6 AWG
	030.015.100	25.4	1	185.0	11.3	23.0	50.7	5	20	40	3, #4 AWG
	030.015.125	31.8	1 1/4	512.6	31.3	52.4	115.6	2	8	15	3, #2 AWG
	030.015.150	38.1	1 1/2	540.5	33.0	56.9	125.5	2	8	15	3, #1/0
	030.015.200	50.8	2	1203.9	73.5	124.8	275.2	1	4	6	3, #4/0
	030.015.250	63.5 S	2 1/2 S	1577.3	96.3	188.9	416.6	1	3	4	3, #4/0
	-	63.5 L	2 1/2 L	2866.5	174.9	319.0	701.8	1	-	1	3, #300 MCM
	030.015.300	76.2 S	3 S	1850.9	113.0	230.4	508.1	1	3	4	3, #4/0
	-	76.2 L	3 L	2866.5	174.9	280.0	616.0	1	-	1	3, #250 MCM