

Rigid Conduit Bodies, Malleable Iron • for Rigid • IMC conduit


Application:
To provide access to
conductors for pulling, splicing
and maintenance.

Features:
• Tapered threaded hubs - NPT
• Suitable for use in concrete

Standard Materials:
Malleable iron


Standard Finish:
Zinc plated with
Aluminum enamel paint

**Applicable Third Party
Standards:**
UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1



Threaded LB Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
030.065.050	1/2"	4-11/16"	1-5/16"	2-1/16"	70	70.6
030.065.074	3/4"	5-3/8"	1-1/2"	2-1/4"	36	96.7
030.065.100	1"	6-3/16"	1-13/16"	2-5/8"	48	142.7
030.065.125	1-1/4"	8-1/8"	2-5/8"	2-3/4"	12	287.3
030.065.150	1-1/2"	8-1/8"	2-5/8"	2-13/16"	10	331.5
030.065.200	2"	10-1/2"	3-1/8"	4-7/16"	12	534.1
030.065.250	2-1/2"	13-5/8"	4-5/16"	5-3/8"	4	1105.0
030.065.300	3"	13-7/8"	4-5/16"	5-7/8"	4	1160.3
030.065.350	3-1/2"	16-1/4"	5-5/8"	6-7/8"	2	1989.0
030.065.400	4"	16-5/8"	5-5/8"	7-3/16"	2	2099.5



Threaded C Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
030.085.050	1/2"	5-3/8"	1-5/16"	1-3/8"	48	98.2
030.085.074	3/4"	6"	1-1/2"	1-11/16"	48	118.4
030.085.100	1"	7-1/16"	1-13/16"	1-7/8"	42	169.7
030.085.125	1-1/4"	9"	2-5/8"	2-3/4"	10	309.4
030.085.150	1-1/2"	9"	2-5/8"	2-13/16"	15	368.3
030.085.200	2"	11-1/2"	3-1/8"	3-5/16"	12	552.5
030.085.250	2-1/2"	15"	4-5/16"	3-7/8"	6	1215.5
030.085.300	3"	15-1/8"	4-5/16"	4-3/4"	4	1436.5
030.085.350	3-1/2"	18-1/8"	4-7/8"	5-5/8"	2	2210.0
030.085.400	4"	18-1/8"	4-7/8"	5-5/8"	2	2320.5

