

Rigid Conduit Bodies, Malleable Iron • for Rigid • IMC conduit


Application:
 To provide access to
 conductors for pulling, splicing
 and maintenance.

Features:
 • Tapered threaded hubs - NPT
 • Suitable for use in concrete

Standard Materials:
 Malleable iron


Standard Finish:
 Zinc plated with
 Aluminum enamel paint

**Applicable Third Party
 Standards:**
 UL Standard: 514A
 Fed. Spec. W-C-586D
 NEMA: FB-1



Threaded LL Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
030.070.050	1/2"	4-11/16"	2-1/16"	1-3/8"	70	76.3
030.070.075	3/4"	5-3/8"	2-1/4"	1-11/16"	72	94.7
030.070.100	1"	6-3/16"	2-5/8"	1-7/8"	50	138.1
030.070.125	1-1/4"	8-1/8"	2-3/4"	2-3/4"	15	309.4
030.070.150	1-1/2"	8-1/8"	3-1/2"	2-13/16"	12	331.5
030.070.200	2"	10-1/2"	4-1/8"	3-5/16"	12	497.3
030.070.250	2-1/2"	13-5/8"	4-11/16"	3-7/8"	6	1105.0
030.070.300	3"	13-7/8"	5-7/8"	4-3/4"	4	1436.5
030.070.350	3-1/2"	16-1/4"	6-1/8"	5-5/8"	2	2320.5
030.070.400	4"	16-1/4"	6-15/16"	5-5/8"	2	2431.0



Threaded LR Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
030.075.050	1/2"	4-11/16"	2-1/16"	1-3/8"	70	71.0
030.075.075	3/4"	5-3/8"	2-1/4"	1-11/16"	72	100.0
030.075.100	1"	6-3/16"	2-5/8"	1-7/8"	30	156.5
030.075.125	1-1/4"	8-1/8"	2-3/4"	2-3/4"	15	331.5
030.075.150	1-1/2"	8-1/8"	2-13/16"	2-13/16"	12	345.3
030.075.200	2"	10-1/2"	4-7/16"	3-5/16"	12	626.2
030.075.250	2-1/2"	13-5/8"	5-3/8"	3-7/8"	6	1105.0
030.070.300	3"	13-7/8"	5-7/8"	4-3/4"	4	1436.5
030.070.350	3-1/2"	16-1/4"	6-7/8"	5-5/8"	2	2320.5
030.070.400	4"	16-5/8"	7-3/16"	5-5/8"	2	2500.0

