

Rigid Conduit Bodies, Malleable Iron • for Rigid • IMC conduit


Application:
 To provide access to
 conductors for pulling, splicing
 and maintenance.

Features:
 • Tapered threaded hubs - NPT
 • Suitable for use in concrete

Standard Materials:
 Malleable iron


Standard Finish:
 Zinc plated with
 Aluminum enamel paint

**Applicable Third Party
 Standards:**
 UL Standard: 514A
 Fed. Spec. W-C-586D
 NEMA: FB-1



Threaded T Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
030.080.050	1/2"	5-3/8"	2-1/16"	1-5/16"	60	110.5
030.080.075	3/4"	6"	2-1/4"	1-1/2"	40	137.0
030.080.100	1"	7-1/16"	2-5/8"	1-13/16"	25	196.4
030.080.125	1-1/4"	9"	2-3/4"	2-5/8"	15	331.5
030.080.150	1-1/2"	9"	3-1/2"	2-5/8"	12	368.3
030.080.200	2"	11-1/2"	4-1/8"	3-1/8"	5	663.0
030.080.250	2-1/2"	15"	5-11/16"	4-5/16"	4	1270.8
030.080.300	3"	15-1/8"	5-7/8"	4-5/16"	4	1547.0
030.080.350	3-1/2"	18-1/8"	6-13/16"	4-7/8"	2	2541.5
030.080.400	4"	18-1/8"	7-3/16"	4-7/8"	2	2541.5



Threaded TB Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
030.090.050	1/2"	5-1/4"	1-5/16"	1-5/16"	42	88.4
030.090.075	3/4"	6-1/16"	1-9/16"	1-9/16"	60	119.7
030.090.100	1"	7-1/8"	1-13/16"	1-13/16"	28	197.3
030.090.125	1-1/4"	9-5/16"	2-7/16"	3-3/4"	15	342.6
030.090.150	1-1/2"	9-5/16"	2-9/16"	3-3/4"	15	419.9
030.090.200	2"	11-13/16"	3-3/16"	4-1/8"	8	690.6