

Rigid Conduit Bodies, Malleable Iron • for Rigid • IMC conduit

Application:
To provide access to conductors for pulling, splicing and maintenance.


Features:
• Tapered threaded hubs - NPT
• Suitable for use in concrete

Standard Materials:
Malleable iron

Standard Finish:
Zinc plated with
Aluminum enamel paint

Applicable Third Party Standards:

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1



Threaded X Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
030.095.050	1/2"	5-7/16"	2-13/16"	1-3/4"	42	138.8
030.095.075	3/4"	6-1/16"	2-15/16"	2"	30	172.1
030.095.100	1"	7-1/8"	3-9/16"	2-1/4"	21	246.8
030.095.125	1-1/4"	9-1/8"	4-7/16"	2-9/16"	12	416.4
030.095.150	1-1/2"	9-1/8"	4-7/16"	2-3/4"	12	462.6
030.095.200	2"	11-3/4"	5-3/8"	3-7/16"	6	832.7

Watertight Rigid Conduit Bodies with Stamped Steel Cover & Neoprene Gasket, Malleable Iron • for Rigid • IMC conduit

Application:
To provide access to conductors for pulling, splicing and maintenance.

Features:
Conduit Body
• Tapered threaded hubs - NPT
• Suitable for use in concrete
• NEMA 4 Watertight
Watertight Cover
• Raised dome
• Captive screws

Standard Materials:
Malleable iron
Stamped steel cover
Gasket - Neoprene rubber
Stainless steel screws
Nylon washers


Standard Finish:
Zinc plated with
Aluminum enamel paint

Applicable Third Party Standards:

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1
NEMA 4

The only Malleable Iron
Conduit Bodies
Watertight Rated Type
NEMA 4.

Protected from dirt,
rain, sleet, snow,
windblown dust, splash -
ing water, hose-directed
water and ice build up.



Raised Dome Stamped Steel Conduit Body Cover & Neoprene Gasket. For Rigid • IMC conduit

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	WEIGHT PER C
030.102.050	1/2"	3-15/16"	1-3/8"	3/8"	11.3
030.102.075	3/4"	4-11/16"	1-5/8"	7/16"	15.0
030.102.100	1"	5-3/8"	1-7/8"	7/16"	21.7
030.102.150	1-1/4" - 1-1/2"	7-1/4"	2-5/8"	1/2"	36.3
030.102.200	2"	9-9/16"	3-1/4"	5/8"	56.3
030.102.300	2-1/2" - 3"	12-5/16"	4-7/16"	7/8"	100.7
030.102.400	3-1/2" - 4"	14-7/8"	5-11/16"	7/8"	150.5